

Polymer Melt Rheometer

SmartMelt Series



The New Standard in Polymer Melt Rheology



Find out more

The SmartMelt series empowers users to obtain full shear-rheological profiles including flow curves, oscillation, creep, and relaxation tests – way beyond one-point methods like Melt Flow Index (MFI). Compliant with ASTM D4440, SmartMelt delivers top-quality measurements that position you at the forefront of your industry.

What sets SmartMelt apart?

- Best-in-class temperature control – the most budget-friendly and best-performing electrical temperature oven on the market, with a temperature gradient of almost zero within the sample.
- Fast, user-friendly operation – automatic recognition of accessories and one-handed coupling ensure rapid setup in seconds, effortless measurement, and consistent results.
- Sustainable and efficient – benefit from low compressed gas and energy consumption, as well as quiet operation.



SmartMelt 73

SmartMelt 73 is a polymer melt rheometer for routine measurements. It offers the smallest footprint and the most sustainable, energy-efficient operation.

SmartMelt 303


SmartMelt 303 is an advanced polymer melt rheometer with all the comfort and flexibility you're used to from the Anton Paar MCR series. It's also suitable for the measurement of thermoplastics with high viscosity and high filler content.

Accelerate Your Analysis


A series of tools ensures that operators are trained in no time, optimizes time-to-measurement, and delivers reliable polymer melt rheology results.




1. **Toolmaster:** Automatic recognition of measuring geometry and cell.
2. **QuickConnect:** One-handed coupling of the measuring geometry in seconds.
3. **Gas purging of sample:** Gas purge for samples requiring an inert environment.
4. **RheoCompass templates:** Pre-prepared measuring workflows.
5. **RheoCompass analysis:** Various regression models, curve analysis, master curve based on time-temperature superposition (TTS), and much more.
6. **Automatic data exchange:** With a lab information management system (LIMS) and report export.
7. **Sample preparation and cleaning tools**
8. **Touchscreen:** Full sample preparation directly at the instrument.




Complex viscosity: Complex viscosity of polystyrene at 230 °C. Automatic analysis of zero-shear viscosity based on the Carreau-Yasuda model. (green = regression; red = frequency sweep)



Frequency sweep: Frequency sweep of a polyethylene at 180 °C. Automatic analysis of the cross-over point.



Time-temperature superposition (TTS): Frequency sweeps of polystyrene at 160 °C (blue), 200 °C (red), 260 °C (green), and its appropriate master curve at the reference temperature 200 °C.



Curing: Curing reaction of a silicone at 90 °C. Automatic analysis of the cross-over time (o) and degree of cure (DOC) of 90 % (x).

	SmartMelt 73	SmartMelt 303
Specifications		
Bearing design	Air, fine-pored carbon	
Motor design	Electronically commutated (EC) – permanent magnet synchronous motor	
Displacement transducer	High-resolution optical encoder	
Minimum torque (rotation)	0.1 μ Nm	5 nNm
Minimum torque (oscillation)	0.1 μ Nm	1 nNm
Maximum torque	160 mNm	215 mNm
Minimum angular deflection (set value)	1 μ rad	0.5 μ rad
Maximum angular deflection (set value)	∞ μ rad	
Maximum speed	2,500 rpm	3,000 rpm
Minimum angular frequency¹⁾	2×10^{-5} Hz	2×10^{-8} Hz
Maximum angular frequency	100 Hz	200 Hz
Normal force measurement design	\times	360° capacitive sensor, non-contacting, fully integrated in bearing
Normal force range	\times	-50 N to +50 N
Temperature device		
Temperature oven design	Electrical temperature oven	
Recommended measuring geometry	Plate-plate, disposables	Plate-plate, cone-plate, disposables
Temperature range	-150 °C to +400 °C	
Maximum heating rate	50 °C/min	
Maximum cooling rate	Up to 100 °C/min ²⁾	
Fully automatic temperature calibration	\checkmark	\checkmark
Features		
Ready for extensional, pressure, and powder rheology, tribology, rheo-optics, and more	\times	\checkmark
TruStrain – sample adaptive controller	\times	\checkmark
QuickConnect	\checkmark	\checkmark
Toolmaster	\checkmark	\checkmark
Master curve software analysis module	\checkmark	\checkmark
Automatic gap control/setting, AGC/AGS	\checkmark	\checkmark
Dimensions of rheometer		
Dimensions (W x H x D)	442 mm x 725 mm x 596 mm	453 mm x 725 mm x 673 mm
Weight	45 kg	48 kg

Trademarks Toolmaster (3623873), TruStrain (9176918), RheoCompass (9177015)

\checkmark Included \times Not included

1) Set frequencies below 10^{-4} rad/s are of no practical relevance due to the measuring point duration >1 day

2) Maximum cooling rate depends on the coolant media used: 100 °C/min with fluid, 70 °C/min with liquid N₂, 10 °C/min with air

The Rheo Academy



Find out more

Sign up for our rheology courses and webinars

We regularly offer courses at our global subsidiaries and also organize online or exclusive group courses for customers on request.

Learn the basics of rheology, optimize your work with the RheoCompass software, and gain application-specific knowledge. You can also learn more about specialist subjects and meet our experts for discussions online by taking part in one of our free webinars.

Enjoy access to an extensive database of knowledge

As a customer, enjoy access to a large database of useful application reports, product documentation, and tutorial videos. Benefit from our comprehensive background knowledge on rheological theory (e.g., through our wiki and the book *Applied Rheology* by renowned expert Thomas Mezger).

Get in touch with our experts

We provide excellent service and support. With Anton Paar subsidiaries and numerous partners worldwide, a rheological expert is close to you and happy to help. Call us for advice on test definitions or to discuss the rheological challenges you're facing.



Reliable. Compliant. Qualified.



Our well-trained and certified technicians are ready to keep your instrument running smoothly.

Maximum uptime | Warranty program | Short response times | Global service network

